

Crawford Replacement Kit

Improve your sliding door installation

The Crawford replacement kit makes it possible to improve and upgrade your existing sliding door installation, regardless of brand, and without the need for any architectural adjustments.

The control unit and operator kit is simply installed in your existing sliding door. All remaining components, such as impulse donors, electrical lock, security accumulators and terminal equipment remain intact and are connected to the new Crawford control unit.

Crawford can support your business with any door service you need.

Our team of skilled service engineers prides itself on understanding your needs and matching our service to those needs. Based on the role of your automatic entrance doors and the intensity with which you use them, you can receive service and spare parts that provide the perfect balance of economy, safety and security.

The Crawford sliding door replacement kit offers:

- One solution for all sliding doors
- Instant availability of parts with short installation time
- Easy programming of control unit

Technical information Replacement Kit

Power supply	230 VAC, 47-63 Hz
Max power consumption	1000 W
Power consumption at rest	<3 w
Motor type	24 DC Brush
Voltage Programmable in/output	3 (+ 12/24V DC)
Interlock	Available as standard
Ambient	0-50° C/80% RV
Dimensions (Length)	Max 6500 mm
Max daylight width	3050 mm
Max door weight	250 kg
Opening and closing speed	Fully adjustable
Opening hold time	Adjustable from 1-60 sec
International standards	93/68/EEC (CE) 73/23/EEC (LVD) NEN-EN-IEC 60335-1 IEC 60335-2-103 89/336/EEC (EMC) NEN-EN 12650-1, 12650-2

